

GENERAL SPECIFICATIONS

1. PREFILTER FRAME, TOP HOUSING AND SIDES ARE FABRICATED FROM 1/16" STRUCTURAL ALUMINUM WITH CLEAR ANODIZED FINISH.
2. 10" DIA. BLOWER WITH 1/4 HP 3 SPEED (HI/MED/LO) PERMANENT SPLIT CAPACITOR (3.8 AMP MOTOR, 277/1/60).
3. ULPA FILTER: 3" HEIGHT WITH ANODIZED ALUMINUM FRAME.
4. PREFILTER: 20 % EFF. PLEATED TYPE FARR 30/30 OR EQUAL NOM. 20" X 20" X 1".
5. POWER ON/OFF SWITCH.
6. FAN SPEED CONTROLLED BY A 3 POSITION SWITCH.
7. 3/8-16 EYEBOLTS PROVIDED IN TOP (4) CORNERS FOR CONNECTION TO SUSPENSION SYSTEM.
8. EACH MODULE IS FACTORY TESTED TO MEET UL STANDARDS.
9. EACH MODULE IS INDIVIDUALLY CARTONED FOR PROTECTION DURING SHIPPING.
10. FACE SCREEN: ANODIZED ALUMINUM, 1/8" HOLES ON 1/4" STG CENTERS. WILL PROVIDE AIR FLOW UNIFORMITY.
11. VARIABLE SPEED CONTROL SHIPPED LOOSE WITH UNIT.
12. WALK GRID SPECIFICATIONS: 11 GA STEEL, GALVANIZED FINISH, UNIFORM LOAD CAPACITY = 848 LBS/SQ FT, WITH DEFLECTION = 1/16" (OVER A 48" SPAN) INSTALLED BY OTHERS.

